



Model	dimension(mm) W×D×H (heater W×D)	weight (kg)	electricity(50/60Hz) electriccapacity(kW)	rated current (A) 380V/400V	supply and drain water
3P-206K	760×410×850 (600×110)	107	3P-380V/400V 6.0kW	10 / 9	
3P-208K	960×410×850 (800×110)	143	3P-380V/400V 8.0kW	13 / 12	
3P-210K	1160×410×850 (1000×110)	168	3P-380V/400V 10.2kW	16 / 15	
3P-212K	1360×410×850 (1200×110)	189	3P-380V/400V 12.0kW	19 / 18	



Model	dimension(mm) W×D×H (heater W×D)	weight (kg)	electricity(50/60Hz) electriccapacity(kW)	rated current (A) 380V/400V	supply and drain water
3P-204KC	610×410×390 (450×110)	79	3P-380V/400V 4.5kW	7 / 7	water supply-3/8 drain and overflow-1
3P-206KC	760×410×390 (600×110)	97	3P-380V/400V 6.0kW	10 / 9	water supply-1/2 drain and overflow-1
3P-208KC	960×410×390 (800×110)	123	3P-380V/400V 8.0kW	13 / 12	water supply-1/2 drain and overflow-1
3P-210KC	1160×410×390 (1000×110)	154	3P-380V/400V 10.2kW	16 / 15	water supply-1/2 drain and overflow-1
3P-212KC	1360×410×390 (1200×110)	169	3P-380V/400V 12.0kW	19 / 18	water supply-1/2 drain and overflow-1