



Model	dimension(mm) W×D×H (heater W×D)	weight (kg)	electricity(50/60Hz) electriccapacity(kW)	rated current (A) 380V/400V	supply and drain water
GO-10	770×650×1040 (520×270)	243	3P-380V/400V 10.2kW	16 / 15	
GO-12	820×650×1040 (610×270)	280	3P-380V/400V 12.0kW	19 / 18	
GO-15	870×650×1040 (690×300)	303	3P-380V/400V 15.0kW	23 / 22	
GO-18	1020×650×1040 (820×300)	345	3P-380V/400V 18.0kW	28 / 26	water supply-1/2 drain and overflow-1
GO-21	1020×700×1040 (820×350)	369	3P-380V/400V 21.0kW	32 / 31	water supply-1/2 drain and overflow-1
GOX-135	1000×550×950 (800×130)	270	3P-380V/400V 13.5kW	21 / 20	water supply-1/2 drain and overflow-1
GOX-200	1050×650×950 (680×270)	340	3P-380V/400V 20.4kW	31 / 30	water supply-1/2 drain and overflow-1



Model	dimension(mm) W×D×H (heater W×D)	weight (kg)	electricity(50/60Hz) electriccapacity(kW)	rated current (A) 380V/400V	supply and drain water
3P-210CS	720×550×350 (520×270)	140	3P-380V/400V 10.2kW	16 / 15	water supply-1/2 drain and overflow-1
3P-212CS	810×550×380 (610×270)	152	3P-380V/400V 12.0kW	19 / 18	water supply-1/2 drain and overflow-1
3P-215CS	890×550×380 (690×300)	178	3P-380V/400V 15.0kW	23 / 22	water supply-1/2 drain and overflow-1
3P-218CS	1020×550×380 (820×300)	198	3P-380V/400V 18.0kW	28 / 26	water supply-1/2 drain and overflow-1
3P-221CS	1020×600×380 (820×350)	233	3P-380V/400V 21.0kW	32 / 31	water supply-1/2 drain and overflow-1